

UL Fire Rated Walls Flex-C Trac Compliance

Flex-C Trac complies with the following generic UL listings.
Please note the minimum gauges per listing and the material width limitations if any.
The Engineer of Record should review listing(s) for specific application compliance.

Flex-C Trac UL Listing Compliance		
UL Listing #	Minimum Gauge	Width Limits
v401	25 ga	2 1/2" only
v410	25 ga	
v412	25 ga	3 1/2" only
v414	20 ga	3 5/8" min.
v418	25 ga	
v419	25 ga	2 1/2" only
v420	0.0329	3 1/2" min.
v438	25 ga	
v439	0.038	3 1/2" min.
v449	25 ga	3 1/2" min.

For UL #'s not on this list please contact us at the numbers listed below. We will research the listing and help you with your determination. You can also contact UL directly at:
Tel: 847-272-8800. At www.ul.com., click on certifications and enter a number under UL File No.

Flex-C Trac Sizes & Gauges		
Flex-C Trac Width	20 Gauge	16 Gauge
2 1/2"	X	
3 1/2"	X	
3 5/8"	X	X
4"	X	X
5 1/2"	X	
6"	X	X
8"	X	X
10"	X	X

Flex-Ability Concepts

5500 West Reno Avenue, Suite 300, Oklahoma City, OK 73127

Toll Free: 866-443-FLEX (3539), Tel: 405-996-5343, Fax: 405-996-5353

E-mail: info@flexabilityconcepts.com, Web: www.flexabilityconcepts.com

**FLEX-ABILITY
CONCEPTS**